



SPLENDOR ROUND DIRECTABLE 350MA



POWERLED(S)	1 x 8 Watt incl.	LENS	40° incl.
CRI	90+	VOLTAGE	230 VAC
GEAR / DRIVER	230 VAC LED	MATERIAL	Aluminium
MOUNTING DEPTH	45 mm	WEIGHT	0,250
CUTOUT SHAPE / SIZE	72 mm	IP	20



SPECIAL: Torsion springs and Leaf springs included.

MODELS

	ARTICLE N°	DESCRIPTION	COLOUR	KELVIN	LUMEN
	051101312702	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	BLACK STRUC.	2700	600
	051101313002	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	BLACK STRUC.	3000	600
	051101312701	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	WHITE STRUC.	2700	600
	051101313001	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	WHITE STRUC.	3000	600
	051101312703	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	ANY RAL	2700	600
	051101313003	SPLENDOR ROUND DIRECTABLE INT. WARM WHITE 350mA	ANY RAL	3000	600